



## Handhållen OTDR

### Funktioner:

- \* optimerade för testning av accessnät och sändarnät.
- \* Portabel, hållbar, stötsäker och fuktsäker
- \* Mätning med bara en knapptryckning
- \* Kortkommando funktioner
- \* Bärbar design
- \* Stor lagringskapacitet (upp till 800 testresultat)
- \* flexibelt gränssnitt (USB / LAN-gränssnitt klar)

### Teknisk data:

| Modell | Våglängd (nm)   | Dynamic Range (dB) | Event Dead Zone (m) | ATT Dead Zone (m) |
|--------|-----------------|--------------------|---------------------|-------------------|
| PG321  | 1310±20/1550±20 | 30/28              |                     | <20               |

|                        |                                                                                       |
|------------------------|---------------------------------------------------------------------------------------|
| distance rang(Km)      | 5m~160km                                                                              |
| pulse width(ns)        | 5ns~10µs                                                                              |
| measurement time       | user-defined(smart link)<br>with real-time measurement function                       |
| distance accuracy(m)   | $\pm(0.5m \pm 0.001\% \times \text{range} + \text{sampling resolution})$              |
| attenuation accuracy   | $\pm 0.01 \text{ dB/dB}$                                                              |
| loss limit(dB)         | 0.01 dB                                                                               |
| loss resolution(dB)    | 0.001 dB                                                                              |
| sampling resolution(m) | 0.1m                                                                                  |
| sampling points        | 64000                                                                                 |
| data storage           | 800 traces                                                                            |
| LCD type               | 4.0 inch TFT colorized LCD                                                            |
| laser adapter          | FC/PC SC/PC                                                                           |
| interface              | USB/RJ45                                                                              |
| battery                | built-in rechargeable Li-ion battery charging<br>time <4 hours working time >10 hours |
| power                  | AC/DC adapter input AC90-240V $\pm 10\%$<br>output DC18V                              |
| operating temperature  | 0°C~40°C                                                                              |
| storage temperature    | -10°C~50°C                                                                            |
| relative humidity      | <80%                                                                                  |
| weight                 | <1.5Kg                                                                                |
| dimensions (mm)        | 247×130×67mm                                                                          |

**Pris: Enligt offert**